Warranty period - 12 months from the date of sale, but not more than 18 months from the date of manufacture.

Service life is 5 years from the date of manufacture.

In the presence of mechanical, electrical or other types of damage caused by improper transportation, storage, operation or actions of third parties, no claims for quality are accepted and no warranty repair is performed.

5. CONTENTS OF DELIVERY.

Exit Button KB-3 ..... 1 pcs.
Fixing kit ..... 1 pcs.
Passport ..... 1 pcs.
Packing package..... 1 pcs.

6.■"ÌÙÛÐÍÐÊÈÛÌ■ÖÍ■ÈÊÊÌ×ÛÈÕÊÌ

The exit button KB-3 meets the specifications and is considered suitable for operation.

Release date _____

OTK representative _____ seal

Manufacturer's address:

241024, Russia, Bryansk,
Delegate str., 68.
LLC "METAKOM PLUS"

Тел./fax: (4832) 68-28-26,
тел.: (4832) 68-28-24, 68-28-25.

www: http://www.metakom.ru
e-mail: sales@metakom.ru

AB 32

The product is certified

Exit Button KB-3

PASSPORT

1. PURPOSE.

The exit button KV-3 is designed to work in the intercom system "METAKOM" as a button "Exit", installed at the entrance door indoors. The illumination is located on the front panel of the button. The button has no mechanical contacts and moving parts.

2. SPECIFICATIONS

DC supply voltage, V	12 ... 17
Consumption current, mA (max)	20
Switching voltage, V, no more than	30
Switching current, mA, no more than	70
Operating temperature range, deg. C	-30…+40
Relative air humidity at t = 25C,% (max)	98
Overall dimensions, mm	66x41x8
Weight, kg, no more than	0,12

3. INSTALLATION AND USE INSTALLATION PROCEDURE.

The button is mounted on the door using the mounting kit. Connection to the calling panel and the power supply unit is made in accordance with the passport for this type of call block. When connecting the button, it is necessary to observe the polarity: red wire +12 ... 17V;

white wire - button contact;
green wire - common.

When you touch your finger to the black circle, the contact closes on the common wire.

When installing the button on a metal door, the button may be activated by touching any part of the door. In this case, it is necessary to ensure that the common wire of the button contacts the door.

4. WARRANTY LIABILITIES

The manufacturer guarantees the compliance of the exit button KV-3 to the requirements of TU 6652-59879795-2003 when the user applies the rules of use, storage and transportation.